FNF Construction, Inc.

Recycle with Asphalt Rubber

Due to the superior performance of Asphalt Rubber Caltrans and many California Agencies have adopted a reduced thickness design guideline of 50% for reflective cracking compared to conventional asphalt hot mix. This reduction in overlay thickness makes Asphalt Rubber significantly cheaper than conventional asphalt.

Caltrans 50% Reduced Thickness Design Guideline

- **Caltrans developed the guidelines in 1992**
- **Since 1992 Caltrans has recycled over 20 Million Tires based on this guide line**
- **YOUR AGENCY CAN DO THE SAME THING**

Caltrans Equivalencies for Field Blended RAC

(Thickness in feet)

DGAC (Dense Graded)	RAC Type G (Asphalt Rubber Gap Graded Mixes)
0.15'	0.10'
0.20'	0.10'

Asphalt Rubber: Over 50 years of recycling through responsible design

Our Asphalt Rubber Binders meetAB338 and CalRecycle grant requirements

FNF—with over 20 years of experience in the Industry

We can assist you with your design. Call us at 949-295-7503 for a free consultation

www.FNFinc.com - info@fnfinc.com

CALIFORNIA:

P.O. Box 5236 - Fullerton, CA 92838
Phone (949) 295-7503

ARIZONA:

115 South 48th Street, Tempe, AZ 85281
Phone: 480.784.2910 | Fax: 480.829.8607