More choice, better quality – The EMC edge

Our tiles are designed for comfort and safety – durable, slip resistant and soft – perfect for fitness centers, yoga studios, daycare centers, retirement homes, home gyms, and more.

"Wow that was pretty terrific service. The tiles arrived on Thursday and are already in place. Looking great."

Christophe Osborn,
Ecole Bilingue de Berkeley

Tech Data

Physical Properties

Test Description	ASTM	Result
Flame Spread	E108	Class A
Flammability	E648	Class II
Toxicity	2859	Pass
Slip Resistance	2075	Lead Free
Skid Resistance	F1677	Dry 0.63, Wet .052
Tensile Strength	E303	Dry 96, Wet 47
Wear Resistance	D412	117.3 psi
UV Resistances	D3884	1.64% Loss/3000c
	QPanel QUV	<3.0/4032 ksqm

Head Impact Attenuation

Product Thickness	Certified Height
1.00"	2 feet
2.50"	6 feet
3.50"	8 feet
3.75"	10 feet

Product Specification

Tile Size	24" X 24" + 1/8"
Tile Thickness	1"
Tile Weight	15.75 lb

ENVIRONMENTAL MOLDING CONCEPTS

14050 Day Street
Moreno Valley, CA 92553
(888) 836-2665
www.EMCMolding.com

Better Quality, More Choice

The EMC EDGE